



## DOSTOPNA TOČKA TP-LINK EAP115 300MB/S (EAP115)

**44,99€**

**SKU:** EAP115

**Kategorije:** [Dostopne točke](#), [Mrežna oprema](#)

## OPIS IZDELKA

|                              | WIRELESS FEATURES                                                                                                                    |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>Wireless Standards</b>    | IEEE 802.11n, IEEE 802.11g, IEEE 802.11b                                                                                             |
| <b>Frequency</b>             | 2.4-2.4835GHz                                                                                                                        |
| <b>Signal Rate</b>           | 11n: Up to 300Mbps(dynamic)<br>11g: Up to 54Mbps(dynamic)<br>11b: Up to 11Mbps(dynamic)                                              |
| <b>Reception Sensitivity</b> | 300M: -71dBm@10% PER<br>150M: -75dBm@10% PER<br>54M: -78dBm@10% PER<br>11M: -93dBm@8% PER<br>6M: -92dBm@10% PER<br>1M: -96dBm@8% PER |



AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227

## WIRELESS FEATURES

### Wireless Functions

Multiple SSIDs □Up to 8 SSIDs□  
Enable/Disable Wireless Radio  
Automatic Channel Assignment  
Transmit Power Control □Adjust Transmit Power on dBm□  
QoS(WMM)  
Rate Limit  
Reboot Schedule  
Wireless Schedule  
Wireless Statistics based on SSID/AP/Client

### Wireless Security

Captive Portal Authentication  
Access Control  
Wireless MAC Address Filtering  
Wireless Isolation Between Clients  
SSID to VLAN Mapping  
Rogue AP Detection  
802.1X Support  
64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK

### Transmission Power

CE:  
≤19dBm(EIRP)  
FCC:  
≤21dBm

## HARDWARE FEATURES

### Interface Button Power Supply Power Consumption Dimensions Antenna Type Mounting

Fast Ethernet (RJ-45) Port \*1□Support IEEE802.3af PoE□  
Reset  
PoE or external 9VDC/0.6A power supply  
2.8W  
7.5×6.8×1.2 in. (189.4×172.3×29.5mm)  
Internal 2\* 4dBi Omni  
Ceiling /Wall Mounting (Kits included)