



AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227



**MONITOR ASUS 61 CM (24,0")
PA248CNV 1920X1200 GRAFIČNO
OBLIKOVANJE 75HZ IPS 5MS HDMI
DISPLAYPORT USB-C 90W DP-OUT
4XUSB3.2 PIVOT ZVOČNIKI
SRGB100% ADAPTIVESYNC RJ45
HDR10 PROART**

214,99€

SKU: PA248CNV

Kategorije: [Monitorji](#), [Poslovni monitorji](#)

OPIS IZDELKA

ASUS ProArt PA248CNV. Diagonala zaslona: 61,2 cm (24.1"), ločljivost zaslona: 1920 x 1200 slikovnih pik, tip HD: Full HD+, odzivni čas: 5 ms, izvorno razmerje stranic: 16:10, slikovni kot, vodoravno: 178°, slikovni kot, navpično: 178°. Vgrajeni zvočniki. Vgrajeno zvezdišče USB, različica zvezdišča USB: 3.2. generacija 1 (3.1 Gen 1). Nosilec VESA, nastavitev višine. Barva izdelka: Črna.

Display Type LED-backlit LCD monitor / TFT active matrix

Energy Class	Class E
Energy Class (HDR)	Class G
Diagonal Size	24"
Viewable Size	24.1"
Adaptive-Sync Technology	VESA Adaptive-Sync
Daisy Chaining	Yes
Built-in Devices	USB 3.2 Gen 1 hub
USB Power Delivery	90 Watt
Panel Type	IPS
Aspect Ratio	16:10
Native Resolution	WUXGA 1920 x 1200 at 75 Hz
Pixel Pitch	0.27 mm
Pixel Per Inch	94
Brightness	300 cd/m ²



Contrast Ratio	1000:1 / 10000000:1 (dynamic)
HDR Format	HDR10
Colour Support	16.7 million colours
Colour Gamut	100% Rec 709, 100% sRGB
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	24 - 75 Hz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Backlight Technology	LED backlight
Features	Trace Free Technology, ASUS QuickFit Virtual Scale, Flicker Free technology, 6-axis colour adjustment, Colour Temperature Selection, Low Blue Light technology, Delta E<2 calibration, 3-sided bezelless, CalMAN Verified, ProArt Preset, ProArt Palette, ProArt Chroma Tune
Colour	Black
Dimensions (WxDxH)	53.3 cm x 21.1 cm x 35.9 cm - with stand (lowest position)
Weight	6.5 kg
Type	Audio Speakers - stereo
Output Power / Channel	2 Watt
Interfaces	Connectivity DisplayPort 1.2 HDMI 1.4 Headphone/microphone combo jack LAN (RJ-45) 4 x USB 3.2 Gen 1 downstream USB-C 3.2 Gen 1 upstream/DisplayPort 1.2 Alt Mode DisplayPort 1.2 (for daisy chain)
Display Position Adjustments	Mechanical Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	180
Rotation Angle	-90/+90
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm
Features	Miscellaneous Security lock slot (cable lock sold separately) UL, TUV GS, VCCI, BSMI, cUL, CB, CCC, TUV Ergo, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, MEPS, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CECP, CEL, RCM, CU, TUV Rheinland Flicker Free Certification, HDCP 1.4, TUV Rheinland Low Blue Light (Software Solution)
Compliant Standards	
Security Slot Type	Kensington security slot



AR-SET d.o.o. Dobravica 10 A 8310 Sentjernej Davčna št.: SI16935381 Tel: 059 048 227	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	19 kWh/1000h
Power Consumption HDR (On mode)	22 kWh/1000h
Power Consumption (Typical)	21 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0 Watt

Dimensions & Weight

Dimensions & Weight Details	Without stand - width: 53.3 cm - depth: 5.8 cm - height: 35.9 cm - weight: 4.4 kg
	With stand (lowest position) - width: 53.3 cm - depth: 21.1 cm - height: 35.9 cm - weight: 6.5 kg
	With stand (highest position) - width: 53.3 cm - depth: 21.1 cm - height: 48.9 cm - weight: 6.5 kg

Dimensions & Weight (Shipping)

Shipping Width	73.5 cm
Shipping Depth	17.7 cm
Shipping Height	44.2 cm
Shipping Weight	8.5 kg

Sustainability Information

TCO Certified	TCO Certified Displays 9
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0