AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227



MONITOR ASUS 61 CM (24,0") PA248CNV 1920X1200 GRAFIČNO OBLIKOVANJE 75HZ IPS 5MS HDMI DISPLAYPORT USB-C 90W DP-OUT 4XUSB3.2 PIVOT ZVOČNIKI SRGB100% ADAPTIVESYNC RJ45 HDR10 PROART

325,99€

SKU: PA248CNV
Kategorije: Monitorji, Poslovni monitorji

OPIS IZDELKA

ASUS ProArt PA248CNV. Diagonala zaslona: 61,2 cm (24.1"), ločljivost zaslona: 1920 x 1200 slikovnih pik, tip HD: Full HD+, odzivni čas: 5 ms, izvorno razmerje stranic: 16:10, slikovni kot, vodoravno: 178°, slikovni kot, navpično: 178°. Vgrajeni zvočniki. Vgrajeno zvezdišče USB, različica zvezdišča USB: 3.2. generacija 1 (3.1 Gen 1). Nosilec VESA, nastavitev višine. Barva izdelka: Črna.

Display Type	LED-backlit LCD monitor / TFT active matrix	
	Energy Class	Class E
	Energy Class (HDR)	Class G
	Diagonal Size	24"
	Viewable Size	24.1"
	Adaptive-Sync Technology	VESA Adaptive-Sync
	Daisy Chaining	Yes
	Built-in Devices	USB 3.2 Gen 1 hub
	USB Power Delivery	90 Watt
	Panel Type	IPS
	Aspect Ratio	16:10
	Native Resolution	WUXGA 1920 x 1200 at 75 Hz
	Pixel Pitch	0.27 mm
	Pixel Per Inch	94
	Brightness	300 cd/m²

Contrast Ratio	1000:1 / 10000000:1 (dynamic)
HDR Format	HDR10
Colour Support	16.7 million colours
Colour Gamut	100% Rec 709, 100% sRGB
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	24 - 75 Hz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Backlight Technology	LED backlight
Features	Trace Free Technology, ASUS QuickFit Virtual Scale, Flicker Free technology, 6-axis colour adjustment, Colour Temperature Selection, Low Blue Light technology, Delta E<2 calibration, 3-sided bezeless, CalMAN Verified, ProArt Preset, ProArt Palette, ProArt Chroma Tune
Colour	Black
Dimensions (WxDxH)	53.3 cm x 21.1 cm x 35.9 cm - with stand (lowest position)
Weight	6.5 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	DisplayPort 1.2 ¦ HDMI 1.4 ¦ Headphone/microphone combo jack ¦ LAN (RJ-45) ¦ 4 x USB 3.2 Gen 1 downstream ¦ USB-C 3.2 Gen 1 upstream/DisplayPort 1.2 Alt Mode ¦ DisplayPort 1.2 (for daisy chain)
	Mechanical
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	180
Rotation Angle	-90/+90
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Compliant Standards	UL, TUV GS, VCCI, BSMI, cUL, CB, CCC, TUV Ergo, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, MEPS, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CECP, CEL, RCM, CU, TUV Rheinland Flicker Free Certification, HDCP 1.4, TUV Rheinland Low Blue Light (Software Solution)
Security Slot Type	Kensington security slot

Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	19 kWh/1000h
Power Consumption HDR (On mode)	22 kWh/1000h
Power Consumption (Typical)	21 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0 Watt
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 53.3 cm - depth: 5.8 cm - height: 35.9 cm - weight: 4.4 kg ¦ With stand (lowest position) - width: 53.3 cm - depth: 21.1 cm - height: 35.9 cm - weight: 6.5 kg ¦ With stand (highest position) - width: 53.3 cm - depth: 21.1 cm - height: 48.9 cm - weight: 6.5 kg
Dimensions & Weight (Shipping)	
Shipping Width	73.5 cm
Shipping Depth	17.7 cm
Shipping Height	44.2 cm
Shipping Weight	8.5 kg
Sustainability Information	
TCO Certified	TCO Certified Displays 9
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0