AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227




# MONITOR ASUS 61 CM (24,0") PA248CNV 1920X1200 GRAFIČNO OBLIKOVANJE 75HZ IPS 5MS HDMI DISPLAYPORT USB-C 90W DP-OUT 4XUSB3.2 PIVOT ZVOČNIKI SRGB100% ADAPTIVESYNC RJ45 HDR10 PROART

**325,99€**

**SKU:** PA248CNV
**Kategorije:** Poslovni monitorji, Monitorji

## OPIS IZDELKA

ASUS ProArt PA248CNV. Diagonala zaslona: 61,2 cm (24.1"), ločljivost zaslona: 1920 x 1200 slikovnih pik, tip HD: Full HD+, odzivni čas: 5 ms, izvorno razmerje stranic: 16:10, slikovni kot, vodoravno: 178°, slikovni kot, navpično: 178°. Vgrajeni zvočniki. Vgrajeno zvezdišče USB, različica zvezdišča USB: 3.2. generacija 1 (3.1 Gen 1). Nosilec VESA, nastavitev višine. Barva izdelka: Črna.

| | | |
|---|---|---|
| Display Type | LED-backlit LCD monitor / TFT active matrix | |
| | Energy Class | Class E |
| | Energy Class (HDR) | Class G |
| | Diagonal Size | 24" |
| | Viewable Size | 24.1" |
| | Adaptive-Sync Technology | VESA Adaptive-Sync |
| | Daisy Chaining | Yes |
| | Built-in Devices | USB 3.2 Gen 1 hub |
| | USB Power Delivery | 90 Watt |
| | Panel Type | IPS |
| | Aspect Ratio | 16:10 |
| | Native Resolution | WUXGA 1920 x 1200 at 75 Hz |
| | Pixel Pitch | 0.27 mm |
| | Pixel Per Inch | 94 |
| | Brightness | 300 cd/m² |

| | |
|---|---|
| Contrast Ratio | 1000:1 / 10000000:1 (dynamic) |
| HDR Format | HDR10 |
| Colour Support | 16.7 million colours |
| Colour Gamut | 100% Rec 709, 100% sRGB |
| Response Time | 5 ms (grey-to-grey) |
| Vertical Refresh Rate | 24 - 75 Hz |
| Horizontal Viewing Angle | 178 |
| Vertical Viewing Angle | 178 |
| Backlight Technology | LED backlight |
| Features | Trace Free Technology, ASUS QuickFit Virtual Scale, Flicker Free technology, 6-axis colour adjustment, Colour Temperature Selection, Low Blue Light technology, Delta E<2 calibration, 3-sided bezeless, CalMAN Verified, ProArt Preset, ProArt Palette, ProArt Chroma Tune |
| Colour | Black |
| Dimensions (WxDxH) | 53.3 cm x 21.1 cm x 35.9 cm - with stand (lowest position) |
| Weight | 6.5 kg |
| | **Audio** |
| Type | Speakers - stereo |
| Output Power / Channel | 2 Watt |
| | **Connectivity** |
| Interfaces | DisplayPort 1.2 ¦ HDMI 1.4 ¦ Headphone/microphone combo jack ¦ LAN (RJ-45) ¦ 4 x USB 3.2 Gen 1 downstream ¦ USB-C 3.2 Gen 1 upstream/DisplayPort 1.2 Alt Mode ¦ DisplayPort 1.2 (for daisy chain) |
| | **Mechanical** |
| Display Position Adjustments | Height, pivot (rotation), swivel, tilt |
| Tilt Angle | -5/+35 |
| Swivel Angle | 180 |
| Rotation Angle | -90/+90 |
| Height Adjustment | 130 mm |
| VESA Mounting Interface | 100 x 100 mm |
| | **Miscellaneous** |
| Features | Security lock slot (cable lock sold separately) |
| Compliant Standards | UL, TUV GS, VCCI, BSMI, cUL, CB, CCC, TUV Ergo, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, MEPS, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CECP, CEL, RCM, CU, TUV Rheinland Flicker Free Certification, HDCP 1.4, TUV Rheinland Low Blue Light (Software Solution) |
| Security Slot Type | Kensington security slot |

| | |
|---|---|
| **Power** | |
| Input Voltage | AC 100-240 V (50/60 Hz) |
| Power Consumption SDR (On mode) | 19 kWh/1000h |
| Power Consumption HDR (On mode) | 22 kWh/1000h |
| Power Consumption (Typical) | 21 Watt |
| Power Consumption Stand by | 0.5 Watt |
| Power Consumption (Off Mode) | 0 Watt |
| **Dimensions & Weight** | |
| Dimensions & Weight Details | Without stand - width: 53.3 cm - depth: 5.8 cm - height: 35.9 cm - weight: 4.4 kg ¦ With stand (lowest position) - width: 53.3 cm - depth: 21.1 cm - height: 35.9 cm - weight: 6.5 kg ¦ With stand (highest position) - width: 53.3 cm - depth: 21.1 cm - height: 48.9 cm - weight: 6.5 kg |
| **Dimensions & Weight (Shipping)** | |
| Shipping Width | 73.5 cm |
| Shipping Depth | 17.7 cm |
| Shipping Height | 44.2 cm |
| Shipping Weight | 8.5 kg |
| **Sustainability Information** | |
| TCO Certified | TCO Certified Displays 9 |
| ENERGY STAR Certified | Yes |
| ENERGY STAR Version | 8.0 |