



**MONITOR DELL 130,8 CM (51,5")
U5226KW 6144X2560 CURVED
120HZ IPS 5MS 2XHDMI
2XDISPLAYPORT THUNDERBOLT4
3XUSB-C 140W 4XUSB3.2 2XUSB-C-
OUT HAS ZVOČNIKI 2X9W 3H DCI-
P3-99% RJ45 KVM**

3.326,99€

SKU: U5226KW

Kategorije: [Monitorji](#), [Ukrivljeni monitorji](#)

OPIS IZDELKA

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Label QR Code URL	Https://eprel.ec.europa.eu/qr/2415042
Energy Class	Class G
Diagonal Size	52"
Viewable Size	51.5"
Built-in Devices	USB 3.2/USB-C hub
USB Power Delivery	140 Watt
Panel Type	IPS Black
Aspect Ratio	21:9
Native Resolution	6K 6144 x 2560 at 120 Hz
Pixel Pitch	0.19644 mm
Pixel Per Inch	129
Brightness	400 cd/m ²
Contrast Ratio	2000:1
Colour Support	1.07 billion colours
Colour Gamut	100% sRGB (CIE 1931), 99% DCI-P3 (CIE 1976), 100% BT.709 (CIE 1931), 99% P3 (CIE 1976)
Response Time	5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Vertical Refresh Rate	48 - 120 Hz
Horizontal Refresh Rate	30 - 326 kHz



Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating, low reflection coating
Backlight Technology	LED backlight
Features	Picture in picture, picture by picture, LED edgelight system, Mercury free, arsenic-free glass, Delta E<1.5 calibration
Dimensions (WxDxH)	122.332 cm x 25.5 cm x 66.679 cm - with stand (highest position)
Weight	17.76 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	9 Watt
Connectivity	
Interfaces	2 x HDMI
	2 x DisplayPort 1.4
	Thunderbolt 4/USB-C 3.2 Gen 2 upstream/DisplayPort 1.4 (power up to 140W)
	3 x USB-C upstream (data only)
	4 x USB 3.2 Gen 2 downstream (SuperSpeed USB (10 Gbps))
	LAN (RJ-45)
VESA Mounting Interface	2 x USB-C 3.2 Gen 2 downstream (power up to 27W)
	USB 3.2 Gen 2 downstream with Battery Charging 1.2
	Mechanical
VESA Mounting Interface	100 x 100 mm, 200 x 200 mm, 200 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), ambient light sensor, VESA interface support
	1 x HDMI cable - 1.8 m
Cables Included	1 x DisplayPort 1.4 cable - DisplayPort to DisplayPort - 1.8 m
	1 x Thunderbolt 4 cable - 2 m
	1 x USB-C to USB-A cable - 1 m
Compliant Standards	Plug and Play, RoHS, TUV Rheinland Low Blue Light Certification, BFR-free, PVC-free
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	63.6 kWh/1000h
Power Consumption (Typical)	51.4 Wh
Power Consumption (Max)	430 Watt
Power Consumption Stand by	0.5 Watt



Power Consumption (Off Mode) 0.3 Watt
AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227

Software / System Requirements

Included Software Dell Display Manager, Dell Peripheral Manager

Dimensions & Weight

Dimensions & Weight Details

With stand (highest position) - width: 122.332 cm - depth: 25.5 cm - height: 66.679 cm - weight: 17.76 kg

With stand (lowest position) - width: 122.332 cm - depth: 25.5 cm - height: 57.679 cm - weight: 17.76 kg

Without stand - width: 122.332 cm - depth: 11.194 cm - height: 52.905 cm - weight: 12.95 kg

Dimensions & Weight (Shipping)

Shipping Weight 34.85 kg

Sustainability Information

TCO Certified

TCO Certified Edge Displays, TCO Certified, generation 10, for displays

EPEAT Compliant

EPEAT Gold