AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227



# MONITOR DELL 130,8 CM (51,5") U5226KW 6144X2560 CURVED 120HZ IPS 5MS 2XHDMI 2XDISPLAYPORT THUNDERBOLT4 3XUSB-C 140W 4XUSB3.2 2XUSB-C-OUT HAS ZVOČNIKI 2X9W 3H DCI-P3-99% RJ45 KVM

**2.730,99€**

**SKU:** U5226KW
**Kategorije:** Monitorji, Ukrivljeni monitorji

## OPIS IZDELKA

### General

| | |
|---|---|
| Display Type | LED-backlit LCD monitor / TFT active matrix |
| Energy Label QR Code URL | Https://eprel.ec.europa.eu/qr/2415042 |
| Energy Class | Class G |
| Diagonal Size | 52" |
| Viewable Size | 51.5" |
| Built-in Devices | USB 3.2/USB-C hub |
| USB Power Delivery | 140 Watt |
| Panel Type | IPS Black |
| Aspect Ratio | 21:9 |
| Native Resolution | 6K 6144 x 2560 at 120 Hz |
| Pixel Pitch | 0.19644 mm |
| Pixel Per Inch | 129 |
| Brightness | 400 cd/m² |
| Contrast Ratio | 2000:1 |
| Colour Support | 1.07 billion colours |
| Colour Gamut | 100% sRGB (CIE 1931), 99% DCI-P3 (CIE 1976), 100% BT.709 (CIE 1931), 99% P3 (CIE 1976) |
| Response Time | 5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal) |
| Vertical Refresh Rate | 48 - 120 Hz |
| Horizontal Refresh Rate | 30 - 326 kHz |

| | |
|---|---|
| Horizontal Viewing Angle | 178 |
| Vertical Viewing Angle | 178 |
| Screen Coating | Anti-glare, 3H Hard Coating, low reflection coating |
| Backlight Technology | LED backlight |
| Features | Picture in picture, picture by picture, LED edgelight system, Mercury free, arsenic-free glass, Delta E<1.5 calibration |
| Dimensions (WxDxH) | 122.332 cm x 25.5 cm x 66.679 cm - with stand (highest position) |
| Weight | 17.76 kg |
| | **Audio** |
| Type | Speakers - stereo |
| Output Power / Channel | 9 Watt |
| | **Connectivity** |
| Interfaces | 2 x HDMI<br>2 x DisplayPort 1.4<br>Thunderbolt 4/USB-C 3.2 Gen 2 upstream/DisplayPort 1.4 (power up to 140W)<br>3 x USB-C upstream (data only)<br>4 x USB 3.2 Gen 2 downstream (SuperSpeed USB (10 Gbps))<br>LAN (RJ-45)<br>2 x USB-C 3.2 Gen 2 downstream (power up to 27W)<br>USB 3.2 Gen 2 downstream with Battery Charging 1.2 |
| | **Mechanical** |
| VESA Mounting Interface | 100 x 100 mm, 200 x 200 mm, 200 x 100 mm |
| | **Miscellaneous** |
| Features | Security lock slot (cable lock sold separately), ambient light sensor, VESA interface support |
| Cables Included | 1 x HDMI cable - 1.8 m<br>1 x DisplayPort 1.4 cable - DisplayPort to DisplayPort - 1.8 m<br>1 x Thunderbolt 4 cable - 2 m<br>1 x USB-C to USB-A cable - 1 m |
| Compliant Standards | Plug and Play, RoHS, TUV Rheinland Low Blue Light Certification, BFR-free, PVC-free |
| Security Slot Type | Kensington security slot |
| | **Power** |
| Input Voltage | AC 100-240 V (50/60 Hz) |
| Power Consumption SDR (On mode) | 63.6 kWh/1000h |
| Power Consumption (Typical) | 51.4 Wh |
| Power Consumption (Max) | 430 Watt |
| Power Consumption Stand by | 0.5 Watt |

| | |
|---|---|
| Power Consumption (Off Mode) | 0.3 Watt |
| | **Software / System Requirements** |
| Included Software | Dell Display Manager, Dell Peripheral Manager |
| | **Dimensions & Weight** |
| Dimensions & Weight Details | With stand (highest position) - width: 122.332 cm - depth: 25.5 cm - height: 66.679 cm - weight: 17.76 kg<br>With stand (lowest position) - width: 122.332 cm - depth: 25.5 cm - height: 57.679 cm - weight: 17.76 kg<br>Without stand - width: 122.332 cm - depth: 11.194 cm - height: 52.905 cm - weight: 12.95 kg |
| | **Dimensions & Weight (Shipping)** |
| Shipping Weight | 34.85 kg |
| | **Sustainability Information** |
| TCO Certified | TCO Certified Edge Displays, TCO Certified, generation 10, for displays |
| EPEAT Compliant | EPEAT Gold |