



**MONITOR TOUCH IIYAMA 68,6 CM  
(27,0") T2754MSC-B1AG 1920X1080  
POS IPS 4MS VGA HDMI 2XUSB3.0  
ZVOČNIKI PROLITE INTERAKTIVNI  
MONITOR**

**586,99€**

**SKU:** T2754MSC-B1AG

**Kategorije:** [Monitorji](#), [Monitorji na dotik "Touch"](#)



## OPIS IZDELKA

### General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Label QR Code URL	<a href="https://eprel.ec.europa.eu/qr/519606">https://eprel.ec.europa.eu/qr/519606</a>
Energy Class	Class F
Diagonal Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Brightness	300 cd/m <sup>2</sup>
Contrast Ratio	1000:1 / 80000000:1 (dynamic)
Colour Support	16.7 million colours (8-bit)
Response Time	4 ms (grey-to-grey)
Horizontal Refresh Rate	30 - 83 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Screen Coating	Anti-glare
Backlight Technology	LED backlight
OSD Languages	English, German, French, Italian, Portuguese, Polish, Russian, Spanish, Dutch, Japanese



AR-SET d.o.o. Dobravica 10-A-8316 Sentjernej Davčna St.: SI1695581 Tel: 059 048 227	HDCP, Eco-Mode, OSD lock, Projected-Capacitive Touch (PCT) technology, Flicker Free technology, palm rejection function, Blue Light Reducer Function
Features	
Colour	Matte black
Dimensions (WxDxH)	61.2 cm x 12.1 cm x 41.85 cm
Weight	6.6 kg
	<b>Audio</b>
Type	Speakers - stereo
Output Power / Channel	2 Watt
	<b>Input</b>
Type	Touchscreen
Movement Detection Technology	Capacitive
	<b>Connectivity</b>
	VGA
	HDMI
Interfaces	2 x USB 3.0 downstream (Type A) USB 3.0 upstream (Type B) Audio line-in (mini-jack)
	<b>Mechanical</b>
Display Position Adjustments	Height, tilt
Tilt Angle	-5/+90
Height Adjustment	297.5 mm
VESA Mounting Interface	100 x 100 mm
	<b>Miscellaneous</b>
Features	Security lock slot (cable lock sold separately), VESA interface support
Cables Included	1 x USB cable 1 x HDMI cable
MTBF	50,000 hour(s)
Compliant Standards	Plug and Play, DDC-2B, RoHS, WEEE, REACH, ERP, EAC, REACH SvHC, UKCA
Security Slot Type	Kensington security slot
	<b>Power</b>
Input Voltage	(50/60 Hz)
Power Consumption (On mode)	26 W
Power Consumption SDR (On mode)	26 kWh/1000h
Power Consumption (Typical)	27 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt
	<b>Dimensions &amp; Weight (Shipping)</b>
Shipping Width	68.8 cm



Shipping Depth 20.4 cm  
Shipping Height 47.7 cm  
Shipping Weight 8.4 kg  
**Manufacturer Warranty**  
Service & Support Limited warranty - 2 years