

**OSNOVNA PLOŠČA 1200 GIGABYTE
Z490 AORUS PRO AX ATX****369,99€****SKU: Z490-PAX**[MB 1200](#), [Osnovne plošče](#), [Računalniški deli](#)**OPIS IZDELKA****PODNOŽJE:** INTEL LGA1200**ZA PROCESORJE:** Intel 10th Generation Core i7/i5/i3/Pentium/Celeron**FORMAT:** ATX Form Factor 30.5 x 24.4 cm**VEZNI ČIP:** Intel Z490 Express**POMNILNIK:**

4 x DDR4 (5000(O.C.)/4933(O.C.)/4800(O.C.)/ 4700(O.C.)/ 4600(O.C.)/ 4500(O.C.)/ 4400(O.C.)/ 4300(O.C.)/4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2933 / 2800 / 2666 / 2400 / 2133 MHz) do skupno 128GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora

GRAFIKA: preko CPU**RAID:** DA (0,1,5,10)**RAZŠIRITVENE REŽE:**

1 x PCIe x16 (x16 mode)

1 x PCIe x16 (x8 mode)

1 x PCIe x16 (x4 mode)

2 x PCIe x1

MREŽNA KARTICA: INTEL 2.5GbE LAN chip (2.5 Gbit/1 Gbit/100Mbit)**ZVOČNA KARTICA:** Realtek ALC1200-VB codec, High Definition Audio, 2/4/5.1/7.1-channel, podpora za S/PDIF Out**NOTRANJI PRIKLJUČKI:**



- 1 x 24-pin ATX main power connector
- 1 x 8-pin ATX 12V power connector
- 1 x 4-pin ATX 12V power connector
- 1 x CPU fan header
- 1 x water cooling CPU fan header
- 4 x system fan headers
- 2 x system fan/water cooling pump headers
- 2 x addressable LED strip headers
- 2 x RGB LED strip headers
- 6 x SATA 6Gb/s connectors
- 2 x M.2 Socket 3 connectors
- 1 x front panel header
- 1 x front panel audio header
- 1 x USB Type-C header, with USB 3.2 Gen 1 support
- 1 x USB 3.2 Gen 1 header
- 2 x USB 2.0/1.1 headers
- 2 x Thunderbolt add-in card connectors
- 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)
- 1 x Clear CMOS jumper
- 2 x temperature sensor headers
- 1 x Q-Flash Plus button

ZUNANJI PRIKLJUČKI:

- 1 x USB Type-C port, with USB 3.2 Gen 2 support
- 2 x USB 3.2 Gen 2 Type-A ports (red)
- 3 x USB 3.2 Gen 1 ports
- 4 x USB 2.0/1.1 ports
- 2 x SMA antenna connectors (2T2R)
- 1 x HDMI port
- 1 x RJ-45 port
- 1 x optical S/PDIF Out connector
- 5 x audio jacks

DODATNO:

- iTE I/O Controller Chip
- H/W Monitoring
- Voltage detection
- Temperature detection
- Fan speed detection
- Water cooling flow rate detection
- Overheating warning
- Fan fail warning
- Fan speed control
- BIOS
- 1 x 256 Mbit flash



Use of licensed AMI UEFI BIOS
AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for APP Center

@BIOS

EasyTune

Fast Boot

Game Boost

ON/OFF Charge

RGB Fusion

Smart Backup

System Information Viewer

Support for Q-Flash Plus

Support for Q-Flash

Support for Xpress Install

Bundled Software

Norton Internet Security (OEM version)

cFosSpeed

XSplit Gamecaster + Broadcaster (12 months license)

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/Z490-AORUS-PRO-AX-rev-10#kf>