AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227




# OSNOVNA PLOŠČA 1700 GIGABYTE Z790 AORUS ELITE AX ATX 1XHDMI 1XDISPLAYPORT

**299,99€**

**SKU:** 849467
MB 1700, Osnovne plošče, Računalniški deli

## OPIS IZDELKA

**PODNOŽJE**: INTEL LGA1700
**ZA PROCESORJE**:  Intel 12/13th Generation Core i7/i5/i3/Pentium/Celeron
**FORMAT**: ATX Form Factor 30.5 x 24.4 cm
**VEZNI ČIP**: Intel Z790 Express
**POMNILNIK**:
4 x DDR5 (7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000MHz) do skupno 128GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora, Support for non-ECC / ECC Un-buffered DIMM (operate in non-ECC mode), Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode), Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
**GRAFIKA**: preko CPU
**RAID**: DA (0,1,5,10)
**RAZŠIRITVENE REŽE**:
1 x PCIe 5.0/4.0/3.0 x16 (x16 mode)
2 x PCIe 3.0 x16 (x4 mode)
**MREŽNA KARTICA**: Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) + Wi-Fi 6E AX211 WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.3
**ZVOČNA KARTICA**: Realtek High Definition Audio Audio CODEC
**NOTRANJI PRIKLJUČKI**:
1 x 24-pin ATX main power connector

2 x 8-pin ATX 12V power connectors
1 x CPU fan header
1 x water cooling CPU fan header
3 x system fan headers
1 x system fan/water cooling pump header
2 x addressable LED strip headers
2 x RGB LED strip headers
4 x M.2 Socket 3 connectors
6 x SATA 6Gb/s connectors
1 x front panel header
1 x front panel audio header
1 x USB Type-C header, with USB 3.2 Gen 2 support
1 x USB 3.2 Gen 1 header
2 x USB 2.0/1.1 headers
2 x Thunderbolt add-in card connectors
1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)
1 x reset button
1 x Q-Flash Plus button
1 x Clear CMOS button
1 x reset jumper
1 x Clear CMOS jumper

**ZUNANJI PRIKLJUČKI**:

1 x USB Type-C port, with USB 3.2 Gen 2x2 support
2 x USB 3.2 Gen 2 Type-A ports (red)
3 x USB 3.2 Gen 1 ports
4 x USB 2.0/1.1 ports
2 x SMA antenna connectors (2T2R)
1 x HDMI 2.0 port
1 x DisplayPort
1 x RJ-45 port
1 x optical S/PDIF Out connector
2 x audio jacks

**DODATNO**:

iTE I/O Controller Chip
H/W Monitoring
Voltage detection
Temperature detection
Fan speed detection
Water cooling flow rate detection
Fan fail warning
Fan speed control
BIOS

1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features
Support for GIGABYTE Control Center (GCC)
Support for Q-Flash
Support for Q-Flash Plus
Support for Smart Backup
Bundled Software
Norton Internet Security (OEM version)
LAN bandwidth management software

Spletna stran proizvajalca: https://www.gigabyte.com/Motherboard/Z790-AORUS-ELITE-AX-rev-10#kf