AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227



OSNOVNA PLOŠČA LGA1851 GIGABYTE B860M DS3H WIFI6E MICROATX HDMI 2XDISPLAYPORT

212,99€

SKU: B860M-DS3H-WIFI
MB 1851, Osnovne plošče, Računalniški deli

OPIS IZDELKA

PODNOŽJE: INTEL LGA 1851
ZA PROCESORJE: Intel Core Ultra Processors
FORMAT: micro ATX format 24.4 cm x 24.4 cm
VEZNI ČIP: INTEL B860
POMNILNIK:
4 x DDR5 DIMM ECC/non-ECC 9066(O.C)/8800(O.C) /8600(O.C) / 8400(O.C) /8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) / 7800(O.C) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400 / 5600MHz) do skupno 256GB kapacitete, dual channel
in XMP podpora, ECC/non-ECC podpora
GRAFIKA: DA - preko CPU
RAID: RAID 0, RAID 1, RAID 5, and RAID 10
RAZŠIRITVENE REŽE:
1 x PCI Express 5.0 x16
3 x PCI Express 4.0 x1
MREŽNA KARTICA: Realtek 2.5GbE LAN chip + Intel Wi-Fi 6E AX211 WIFI a, b, g, n, ac, ax + BLUETOOTH 5.3
ZVOČNA KARTICA: Realtek codec High Definition Audio (2/4/5.1/7.1-channel)
NOTRANJI PRIKLJUČKI:
1 x 24-pin ATX main power connector
1 x 8-pin ATX 12V power connector
1 x CPU fan header

1 x CPU fan/water cooling pump header
1 x system fan header
1 x system fan/water cooling pump header
3 x addressable RGB Gen2 LED strip headers
1 x RGB LED strip header
2 x M.2 Socket 3 connectors
4 x SATA 6Gb/s connectors
1 x front panel header
1 x front panel audio header
1 x USB Type-C header, with USB 3.2 Gen 1 support
1 x USB 3.2 Gen 1 header
2 x USB 2.0/1.1 headers
1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)
1 x Q-Flash Plus button
1 x reset jumper
1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

1 x PS/2 keyboard/mouse port
1 x HDMI port (Note)
2 x DisplayPorts (Note)
1 x USB 3.2 Gen 2 Type-A port (red)
2 x USB 3.2 Gen 1 ports
3 x USB 2.0/1.1 ports
2 x antenna connectors (2T2R)
1 x RJ-45 port
3 x audio jacks

DODATNO:

iTE I/O Controller Chip
H/W Monitoring
Voltage detection
Temperature detection
Fan speed detection
Water cooling flow rate detection
Fan fail warning
Fan speed control
BIOS
1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features
Support for GIGABYTE Control Center (GCC)

Support for Q-Flash
Support for Q-Flash Plus
Support for Smart Backup
Bundled Software
Norton Internet Security (OEM version)
LAN bandwidth management software

Spletna stran proizvajalca: https://www.gigabyte.com/Motherboard/B860M-DS3H-WIFI6E#kf