AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227



# POE INJECTOR UBIQUITI NETWORKS U-POE-AF POE ADAPTER 15W/48 V

**10,99€**

**SKU:** U-POE-AF
**Kategorije:** Mrežna oprema, Mrežni pribor

## OPIS IZDELKA

Adapter, ki lahko napaja naprave UniFi PoE z aplikacijami brezžične mreže ali razbremeni odvisnosti od napajanja stikala PoE.

**Lastnosti:**
Zagotavlja do 15W PoE
Združljivo z U6 Mesh, Camera G4 Pro in drugimi napravami PoE
Zaščita pred prenapetostjo, najvišjim impulzom in nadtokovno zaščito
AC kabel z ozemljitvijo
LED indikator za spremljanje stanja

SPECIFIKACIJE:

| | |
|---|---|
| U-POE-af | |
| Dimensions | 86 x 46 x 33 mm |
| | (3.39 x 1.81 x 1.30") |
| Weight | 100 g |
| | (3.53 oz) |
| Output Voltage | 48VDC @ 0.32A |
| LAN Activity Indicator | No |

| | |
|---|---|
| Gigabit LAN Port | Yes |
| Remote Reset Capability | Yes |
| Reset Button | No |
| Rated Voltage | 100-240VAC @ 50/60Hz |
| Input Current | 500mA @ 90VAC |
| Inrush Current | <100A Peak @ 25°C |
| Efficiency | 84.25+% |
| Output Ripple | 200mV p-p |
| Switching Frequency | 65 kHz |
| Line Regulation | ≤ 3% |
| Load Regulation | ≤ 5% |
| 2-Pair Powering | Pins 4, 5 (+) and Pins 7, 8 (-) |
| 4-Pair Powering | – |
| Operating Temperature | 0 to 40° C |
| | (32 to 104° F) |
| Storage Temperature | -30 to 70°C |
| | (-22 to 158° F) |
| Operating Humidity | 5 to 90% Noncondensing |
| AC Connector | IEC-320 C6 |
| Data IN / POE | RJ45 Shielded Socket |
| Surge Protection | Difference and Common Mode |
| Clamping Protection | 11V Data, 60V Power |
| Max. Surge Discharge | 1500A (8/20 µs) Power |
| Peak Pulse Current | 36A (10/1000 µs) Data |
| Shunt Capacitance | <5 pF data |
| Response Time | <1 ns |
| Certifications | CE, FCC, IC, UL |