




**STIKALO 48-PORT MIKROTIK MI
10/100/1000
(CRS354-48P-4S+2Q+RM)**

1.299,99€

SKU: 24002273

Kategorije: [Mrežna oprema](#), [Stikala](#)



OPIS IZDELKA

Novi CRS354-48P-4S + 2Q + RM je učinkovita in prilagodljiva stojna rešitev za upravljanje omrežij v najzahtevnejših okoljih.

Za razliko od mnogih drugih stikal, so izdelki Mikrotik narejeni z mislijo na skrbnika sistema.

To močno stikalo ima 48 x 1G RJ45 vrat in 4 x 10G SFP + vrata ter tudi 2 x 40G QSFP + vrata za izjemno hitre optične povezave ali povezovanje z drugimi napravami s hitrostjo 40 Gbps.

Vseh 48 mrežnih vrat ponuja različne možnosti izhodne moči: pasivni PoE, nizkonapetostni PoE, 802.3af / at (tip 1 "PoE" / tip 2 "PoE +") s samodejnim zaznavanjem, zaradi česar je to stikalo najlažja rešitev za napajanje tudi največjih porabnikov.

Vključen je mogočen napajalnik, ki lahko zagotavlja 750 W moči in poleg je še poseben nosilec za enostavno upravljanje kablov.

CRS354-48P-4S + 2Q + RM je izjemno funkcionalen in bo popoln dodatek k profesionalni uporabi omrežja.

Skupna pretočnost je 168 Gbps, preklopna zmogljivost je 336 Gbps, hitrost posredovanja pa 235 Mpps.

SPECIFIKACIJE:

Details

Product code

CRS354-48P-4S+2Q+RM



Architecture	AR-SET d.o.o. Dobravica 10 A 8510 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227
CPU	MIPSBE
CPU core count	QCA9531
CPU nominal frequency	1
Dimensions	650 MHz
RouterOS license	443 x 382 x 44 mm
Operating System	5
Size of RAM	RouterOS
Storage size	64 MB
Storage type	16 MB
MTBF	FLASH
Tested ambient temperature	Approximately 200'000 hours at 25C
	-20°C to 60°C
Powering	
Details	
Number of AC inputs	1
AC input range	100-240
Max power consumption	800 W
Max power consumption without attachments	85 W
FAN count	4
PoE-out	
Details	
PoE-out ports	Ether1-Ether48
PoE out	802.3af/at
Max out per port output (input 18-30 V)	1000 mA
Max out per port output (input 30-57 V)	570 mA
Total output current	27A at 26V OR 13.2A at 53V
Total output power	700W
Ethernet	
Details	
10/100 Ethernet ports	1
10/100/1000 Ethernet ports	48
Fiber	
Details	
SFP+ ports	4
Number of 40G QSFP+ ports	2
Peripherals	



Details AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227

Serial console port	RJ45
---------------------	------

Other	
-------	--

Details

CPU temperature monitor	Yes
-------------------------	-----

Current Monitor	Yes
-----------------	-----

PCB temperature monitor	Yes
-------------------------	-----

Voltage Monitor	Yes
-----------------	-----

Certification & Approvals	
---------------------------	--

Details

Certification	CE, EAC, ROHS
---------------	---------------

IP	IP20
----	------