



**STIKALO 48-PORT ZYXEL
GS1920-48V2 50PORT SMART
MANAGED SWITCH 44X GIG. COPPER
IN 4X GIGABIT DUAL PERS. HYBRID
MODE STANDALONE ALI
NEBULAFLEX CLOUD**

479,99€

SKU: GS1920-48V2-EU0101F

Kategorije: [Mrežna oprema](#), [Stikala](#)

OPIS IZDELKA

Serijska GS1920 je idealna za uvajanje SMB v več scenarijih, s svojimi edinstvenimi kombinacijami vrat v prihodnosti, ki zagotavljajo enostavno rast po cesti.

Vrsta naprave: Stikalo - 48 vrat - pametno

Vrsta ograjenega ohišja: Stojalo za montažo 1U

Podtip: Gigabitni Ethernet

Pristanišča: 48 x 10/100/1000 + 4 x kombinirani Gigabitni SFP + 2 x Gigabitni SFP

Predstava: Kapaciteta preklopa: 100 Gbps Nastavna stopnja: 75 Mpps

Zmogljivost: QoS strojne čakalne doteka na vrata: 8

Velikost tabele mac naslovov: 16K vnosi

Protokol usmerjanja: IGMPv2, IGMP, IGMPv3

Protokol za daljinsko upravljanje: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c

Funkcije: Nadzor pretoka, podpora za VLAN, IGMP vooping, podpora za Syslog, zrcaljenje vrat, MAC filtriranje adresa, Broadcast Storm Control, IPv6 support, IP address filtering, Multicast Storm Control, Unicast Storm Control, firmware upgradable, Weighted Fair Queuing (WFQ), ZyXEL iStacking Technology, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Kakovost storitve (QoS), podpora RADIUS, mld vooping, DHCP rele, Varnost vrat, SNMP past, DHCP odjemalec, Baza informacija o upravljanju (MIB), Multicast VLAN Registracija (MVR), Dynamic VLAN Support (GVRP), slike dvojnog firmwarea, Strogi prioritetni redosled (SPQ), Protokol za odkrivanje suseda (NDP), izolacija portova, Class of Service (CoS), IGMP proxy, 802.1x authentication, Duplicated Address Detection, cloud



managed, DiffServ Code Point (DSCP) support, 1.5MB buffer paketa, ErrDisable Recovery, IGMP filtriranje, IGMP throttling, Protocol-based VLANs support, CPU protection, IP source guard, ARP inspection, Internet Control Message Protocol (ICMP), VLAN filtering, Loop Guard, Voice VLAN, Private VLAN, Guest VLAN, Guest VLAN, Weighted Round Robin (WRR), MAC based VLAN, VLAN Tagging, port-based VLAN, Unknown Storm Control, MRSTP, MAC freeze

Skladni standardi: IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3az

Moč: AC 120/230 V (50/60 Hz)

Dimenzije (WxDxH): 44 cm x 20 cm x 4,45 cm

Teža: 2,8 kg

Garancija proizvajalca: Omejena življenjska garancija