STIKALO 48-PORT ZYXEL GS1920-48V2 50PORT SMART MANAGED SWITCH 44X GIG. COPPER IN 4X GIGABIT DUAL PERS. HYBRID MODE STANDALONE ALI NEBULAFLEX CLOUD

479,99€

SKU: GS1920-48V2-EU0101F
Kategorije: Mrežna oprema, Stikala

OPIS IZDELKA

Serija GS1920 je idealna za uvajanje SMB v več scenarijih, s svojimi edinstvenimi kombinacijami vrat v prihodnosti, ki zagotavljajo enostavno rast po cesti.

Vrsta naprave: Stikalo - 48 vrat - pametno
Vrsta ograjenega ohišja: Stojalo za montažo 1U
Podtip: Gigabitni Ethernet
Pristanišča: 48 x 10/100/1000 + 4 x kombinirani Gigabitni SFP + 2 x Gigabitni SFP
Predstava: Kapaciteta preklopa: 100 GbpsNastavna stopnja: 75 Mpps
Zmogljivost: QoS strojne čakalne doteka na vrata: 8
Velikost tabele mac naslovov: 16K vnosi
Protokol usmerjanja: IGMPv2, IGMP, IGMPv3
Protokol za daljinsko upravljanje: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c
Funkcije: Nadzor pretoka, podpora za VLAN, IGMP vooping, podpora za Syslog, zrcaljenje vrat, MAC filtriranje adresa, Broadcast Storm Control, IPv6 support, IP address filtering, Multicast Storm Control, Unicast Storm Control, firmware upgradable, Weighted Fair Queuing (WFQ), ZyXEL iStacking Technology, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Kakovost storitve (QoS), podpora RADIUS, mld vooping, DHCP rele, Varnost vrat, SNMP past, DHCP odjemalec, Baza informacija o upravljanju (MIB), Multicast VLAN Registracija (MVR), Dynamic VLAN Support (GVRP), slike dvojnog firmwarea, Strogi prioritetni redosled (SPQ), Protokol za odkrivanje suseda (NDP), izolacija portova, Class of Service (CoS), IGMP proxy, 802.1x authentication, Duplicated Address Detection, cloud

managed, DiffServ Code Point (DSCP) support, 1.5MB pufer paketa, ErrDisable Recovery, IGMP filtriranje, IGMP throttling, Protocol-based VLANS support, CPU protection, IP source guard, ARP inspection, Internet Control Message Protocol (ICMP), VLAN filtering, Loop Guard, Voice VLAN, Private VLAN, Guest VLAN, Guest VLAN, Weighted Round Robin (WRR), MAC based VLAN, VLAN Tagging, port-based VLAN, Unknown Storm Control, MRSTP, MAC freeze
Skladni standardi: IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEEE 802.3az
Moč: AC 120/230 V (50/60 Hz)
Dimenzije (WxDxH): 44 cm x 20 cm x 4,45 cm
Teža: 2,8 kg
Garancija proizvajalca: Omejena življenjska garancija