



AR-SET d.o.o. Dobravica 10 A 8310 Šentjernej Davčna št.: SI16935381 Tel: 059 048 227



UPS BATERIJA HITACHI-CSB /12V 9,0AH (HRL 1234W)

49,99€

SKU: HRL1234W

Kategorije: [Električno napajanje](#), [UPS](#)

OPIS IZDELKA

Standarna dodatna baterija za UPS naprave, priporočamo jo za Socomec UPSe. HRL 1234W F2FR je baterija s podaljšano življensko dobo. Prenese več kot 260 ciklov popolnega praznjenja in polnjenja in v stanju pripravljenosti ima življenko dobo predvidoma 8 let.

Njene lastnosti so majhen volumen, nizka teža in več ciklov polnjenja in praznjenja, kot običajne baterije.

Tehnični opis proizvajalca v angleškem jeziku:

Cells Per Unit

6

Voltage Per Unit

12 V

Capacity

34W @ 15 Minute-Rate to 1.67V Per Cell @ 25°C(77°F)

Weight

Approx. 2.7 kg(5.95 lbs)



Maximum Discharge Current	130A (5 Sec)
---------------------------	--------------

Internal Resistance Approx.	Approx. 17 mΩ
-----------------------------	---------------

Operating Temperature Range	Discharge□-15°C~50°C(5°F~122°F) Charge□-15°C~40°C(5°F~104°F) Storage□-15°C~40°C(5°F~104°F)
-----------------------------	--

Nominal Operating Temperature Range	25°C±3°C(77°F±5°F)
-------------------------------------	--------------------

Float Charging Voltage	13.5 to 13.8 VDC/Unit Average at 25°C(77°F)
------------------------	---

Recommended Maximum Charging Current Limit	3.4A
--	------

Equalization and Cycle Service	14.4 to 15.0 VDC/Unit Average at 25°C(77°F)
--------------------------------	---