



ETH LAN PCI-EXPRESS 100/1000 GIGALAN TP-LINK TG-3468

SKU: 19800

Kategorije: [Ethernet LAN](#), [Mrežna oprema](#), [UPS](#)

OPIS IZDELKA

Mrežna kartica za vgradnjo v PC

V skladu z IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x

Hitrost prenosa podatkov: 10/100/1000 Mbps

Hitrost prenosa podatkov v Full Duplex načinu: 20/200/2000 Mbps

Namestitev slot: PCI-Express x1 (PCIe 1.0a)

Vmesnik: 1x RJ45

FIFO (8K/64K)

LED indikator za povezavo, aktivnost, napake

V skladu z RoHS, CE, FCC

protokol: TCP/IP, CSMA/CD

VEČ PODATKOV

Vmesniki

Tehnologija povezovanja	Žična
Za notranjo vgradnjo	Da
Vmesnik HOST	PCI-E



Vmesnik	Ethernet
Ethernet LAN (RJ-45)	1
Pasovna širina	
Hitrost prenosa podatkov (max)	2000 Mbit/s
Podprte hitrosti prenosa podatkov	10/100/1000 Mbps
Hitrost prenosa podatkov	1 Gbit/s
dupleks	Da
Povezljivost	
Ethernet LAN	Da
Tehnologija kablov	10/100/1000BaseT(X)
Ethernet LAN prenos	10,100,1000 Mbit/s
LAN standardi	IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
Podpora za nadzor pretoka	Da
Podpira Jumbo okvirjev	Da
Protokoli	
Podprti omrežni protokoli	CSMA/CD, TCP/IP
Oblika	
Barva izdelka	green
Splošno	
Prebuditi se-naprej-LAN pripravljen	Da
Podprti operacijski sistemi Win	Windows 2000, Windows 2000 Professional, Windows 98SE, Windows Vista Enterprise, Windows Vista Business, Windows Vista x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Podprti operacijski sistemi Linux	Da
Sistemske zahteve	
Združljivost	PC&Notebook
Certifikati	
Skladnost	FCC, CE
Pogoji uporabe	
Delovna temperatura (TT)	0 - 40 °C



Temperatura skladiščenja (TT)	-40 - 70 °C
-------------------------------	-------------

Delovna relativna vlažnost (HH)	10 - 90%
---------------------------------	----------

Relativna vlažnost skladiščenja (HH)	5 - 90%
--------------------------------------	---------

Ostale lastnosti

Delovna temperatura (TT)	32 - 104 °F
--------------------------	-------------

UPORABNE POVEZAVE

- <http://www.chiligreen.com/shop/datenblaetter/75110059.pdf>