



VOIP USB-SIP-GW2 ADAPTER



SKU: 12236

Kategorije: [Modemi, telefonija,](#)
[Računalniški deli](#)

OPIS IZDELKA

USB VoIP adapter
model SIP-GW2

- Make/Receive both VoIP calls and regular PSTN calls
- Auto-detection and auto-switch to VoIP or PSTN calls
- Phone rings for all incoming VoIP and PSTN calls
- VoIP or PSTN calls selected by phone key (**)
- Supports SIP 2.0(RFC 3261), PPPoE, STUN, DHCP(both client and server) etc.
- Built-in router, NAT, gateway, LAN pass and DMZ port forwarding.
- Support various voice codec including G.711U, G.711A, G.729A.
- Support Caller ID/Name display or block.
- Support call hold, call waiting, call forwarding, and call transfer
- Support in-band and out-of-band DTMF transfer.
- Dial plans, dial tone ,busy tone, ring back tone, alert tone can be set flexible.
- Support silence suppression, VAD, CNG, line echo cancellation (G.168), AGC, and QoS.
- Support standard encryption and authentication (DIGEST using MD5 and MD5-sess).
- Support automated NAT traversal without manual manipulation of firewall/NAT.
- Support firmware upgrade via TFTP, FTP and HTTP.

Priključki:

LAN interface 1 X RJ45 10/100M Base-T

WAN interface 1 X RJ45 10/100M Base-T



FXS telephone port 1×FXS

FXO PSTN port 1×FXO

LED Status, PSTN, VoIP

Universal Switching Power Adaptor Input: 100-240VAC 50-60 Hz Output: +5VDC, 1200mA